

RF AMPLIFIER

MODEL *TM6554*

Available as: TM6554, 4 Pin TO-8 (T4)
 TN6554, 4 Pin Surface Mount (SM3)
 FP6554, 4 Pin Flatpack (FP4)
 BX6554, Connectorized Housing (H1)

Features

- High Gain: 27.5 dB Typical
- Environmental Screening Available

Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point.....+38 dBm (Typ.)
 Second Order Two Tone Intercept Point.....+32 dBm (Typ.)
 Third Order Two Tone Intercept Point.....+19 dBm (Typ.)

Specifications


CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	5 - 400 MHz	5 - 400 MHz
Gain (dB)	27.5	25.0 Min.
Power @ 1 dB Comp. (dBm)	+8	+6.0 Min.
Reverse Isolation (dB)	-35	-34 Max.
VSWR In	<1.5:1	2.0:1 Max.
Out	<1.5:1	2.0:1 Max.
Noise figure (dB)	5	6.0 Max.
Power Vdc	+15	+15
mA	33	38 Max.

Note: Care should always be taken to effectively ground the case of each unit.

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 µsec Max.)

Typical Performance Data



Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.02	-103	23.84	2	.01	5	.18	-8
50	.01	-156	23.68	-24	.01	10	.17	-19
100	.02	-176	23.47	-48	.01	14	.17	-37
200	.04	145	23.18	-96	.01	10	.15	-71
300	.02	108	23.37	-145	.13	12	.12	-110
400	.08	-96	24.69	164	.15	-10	.09	164



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 04/08/05

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001