

# Model 1473

## High Power, N or SMK Connectors

### Conduction Cooled

**DC to 6.0 GHz**  
**500 Watts**



### Features

- /// Precision Connectors with high temperature support beads.
- /// Designed to meet environmental requirements of MIL-DTL-3933.
- /// 10 Kilowatts peak, Conduction Cooled
- /// Wireless Applications - Optimized for use in the communications bands.

### Specifications

**NOMINAL IMPEDANCE:** 50  $\Omega$   
**FREQUENCY RANGE:** DC to 6.0 GHz

MAXIMUM SWR:	
Frequency (GHz)	SWR
DC - 6	1.20

**3rd ORDER INTERMODULATION (1473-X-LIM ONLY):**  
 Reflected Levels (IM3), -100 dBc with two input signals @ 869 MHz and 891 MHz with average carrier power levels of +43 dBm each.

**POWER RATING:** 500 watts **average**, 10 kilowatt **peak** (5  $\mu$ sec pulse width; 2.75% duty cycle) with case temperature held within **100 °C maximum** with appropriate conductive heat sink.

**TEMPERATURE RANGE:** -55°C to 100°C

**TEST DATA:** Swept data plots of SWR from 50 MHz to 6 GHz is available at additional cost.


**CONNECTORS:** Type N connector per MIL-STD-348 interface dimensions - mate nondestructively with MIL-C-39012 connector. Choice of male (-4) or female connector (-3).

SMK (2.92mm) connector mates nondestructively with SMA per MIL-C-39012, 3.5mm and other 2.92mm (SMK) connector. Choice of male (-2) or female connector (-1).

**CONSTRUCTION:** Aluminum alloy body, stainless steel connectors; gold plated beryllium copper contacts and stainless steel male contacts.

**WEIGHT:** 900 g (31.7 oz.)

**PHYSICAL DIMENSIONS:**




Model #	DIM A	Connector Type
1473-1	12.7 (0.50)	2.92mm female
1473-2	14.0 (0.55)	2.92mm male
1473-3	15.0 (0.59)	N female
1473-4	22.9 (0.90)	N male

NOTE: All dimensions are given in mm (inches) and are nominal, unless otherwise specified.

### MODEL NUMBER DESCRIPTION:

Example:



\* Add -LIM to entire model number for Low Intermodulation option.