



CMN538-20


900 MHz Transmit Filter, 20dB Rejection

Revision 2 • May 22, 2007

Passband:	824 to 894 MHz
Passband Insertion Loss:	0.50dB max.
Rejection:	
896 – 901 MHz	20 dB minimum;
Passband Return Loss:	18 dB minimum
Passband Power Handling:	
Average:	500 watts
Peak Instantaneous (PIP):	12500 watts
Operating Altitude:	10,000 Feet maximum
Weatherproofing:	
Housing:	To ETSI 300-19-2-4
Connectors:	Sealed to IP68 (Unmated)
Intermodulation:	-110 dBm maximum w/two +43 dBm carriers
Dimensions:	o1-CMN538-20r2
Mounting:	Rack Mount Tray Outdoor Catwalk (Ice Bridge) Pole Mount
Operating Temperature:	-30°C to +54°C
Storage Temperature:	-40°C to +85°C

NOTES: UNLESS OTHERWISE SPECIFIED

1. FINISH: SEMIGLOSS WHITE EPOXY PAINT, COLOR NO. 27925 PER FED-STD-595A.
2. MARKING: LABEL.
3. CONNECTOR THREADS AND MOUNTING HOLES ARE PAINT FREE.



THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY PROPERTY OF COMMERCIAL MICROWAVE TECHNOLOGY. THIS DOCUMENT IS RECEIVED IN CONFIDENCE AND ITS CONTENTS MAY NOT BE DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF COMMERCIAL MICROWAVE TECHNOLOGY

COMMERCIAL MICROWAVE TECHNOLOGY, INC.

DRAWN:	ID	04/17/2006	TOLERANCES:	SIZE	DWG NO.	REV
ENG:			.XX: ± .01	B	OUTLINE CMN538-20	02
RELEASED:			.XXX: ± .002	CAGE:	1SCX4	
			.XXXX: ± .0005	SHEET	1 OF 1	
			ANGLES: ± 1°			