



CMN538-60

900 MHz Transmit Filter, 60dB Rejection

Revision 5 • August 2007


Passband:	824 to 894 MHz
Passband Insertion Loss:	
824 – 893.5 MHz:	0.50 dB max.
893.5 – 894 MHz:	0.75 dB max.
Ripple (Peak to Peak):	
824 – 893.5 MHz:	0.30 dB max.
893.5 – 894 MHz:	0.60 dB max.
Rejection:	
896 – 901 MHz	60 dB min.
Passband Return Loss:	18.0 dB min.
Passband Power Handling:	
Average:	500 watts @ up to 15,000 feet
Peak Instantaneous (PIP):	12500 watts @ up to 15,000 feet
Weatherproofing:	
Housing:	To ETSI 300-19-2-4
Connectors:	Sealed to IP68 (Unmated)
MHA Support:	5.0 Amps @ 20VDC on Center Conductor
Intermodulation:	-110 dBm maximum w/two +43 dBm carriers
Dimensions:	Per CMT ol-538-60 Rev. 4
Mounting:	Rack Mount Tray Outdoor Catwalk (Ice Bridge) Pole Mount
Operating Temperature:	-30°C to +54°C
Storage Temperature:	-40°C to +85°C

NOTES: UNLESS OTHERWISE SPECIFIED

- 1. FINISH: SEMI-GLOSS GRAY EPOXY PAINT,
COLOR NO. 26493 PER FED-STD-595A
COLOR, 59018 TO INCLUDE.
- 2. MARKING: LABEL, 59018 TO INCLUDE.
CMT PART NUMBER, CUSTOMER PART NUMBER
DATE CODE/SERIAL NUMBER.

CMN538-60
XXXXXX-XX
DC/SN: 0000XXXXXX

3. CONNECTOR THREADS AND MOUNTING HOLES ARE PAINT FREE.



COMMERCIAL MICROWAVE TECHNOLOGY, INC.

DRAWN:	MS	10/31/2005	TOLERANCES:	SIZE	DWG NO.	REV
ENG:			XX: ± .01	A	OUTLINE CMN538-60	04
RELEASED:			.XXX: ± .005	CAGE:	1SCX4	SHEET 1 OF 1
			.XXXX: ± .0005			
			ANGLES: ± 1°			

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY PROPERTY OF COMMERCIAL MICROWAVE TECHNOLOGY. THIS DOCUMENT IS RECEIVED IN CONFIDENCE AND ITS CONTENTS MAY NOT BE DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF COMMERCIAL MICROWAVE TECHNOLOGY