


### FEATURES

- Ultra Low Phase Noise: -169 dBc/Hz
- Multiple RF Outputs
- Automatic Reference Sensing
- DC Voltage Regulation
- Low Current Consumption
- Fully Customizable



These low-phase noise Multiplied PLOs provide the flexibility in the desired output frequency by utilizing a series of x2 multipliers. With an output range of 80 to 1600 MHz, these passive multiplier designs can be configured for most military airborne and ground based applications. With unparalleled phase noise performance of -169 dBc/Hz (at 100 kHz offset), the model BXMF1026 is capable of utilizing either its internal or an external 10 MHz reference. These Multiplied PLOs incorporate unique features including: DC Voltage Regulation, Automatic Reference Sensing, Low Current Consumption and Multiple RF Outputs.




Parameter	Typical	Min. / Max.
Output Frequency	256 MHz	256 MHz
Output Power Level	+6 dBm	+6 dBm
External Reference	10 MHz	10 MHz
Phase Noise at 1 kHz Offset	-149 dBc/Hz	—
Phase Noise at 10 kHz Offset	-168 dBc/Hz	—
Phase Noise at 100 kHz Offset	-169 dBc/Hz	—
Harmonics	-60 dB	—
Spurious	-70 dBc	—
Input VSWR	1.75:1	2.0:1
Output VSWR	1.75:1	2.0:1
Supply Voltage	+12 volts	+12 volts
Supply Current	210 mA	210 mA
Housing Size	5.20" L x 4.00" W x 1.00" H	
RF Connectors	SMA Female	
Operating Case Temp. (Min./Max. Values)	0°C to +70°C (typical values measured at +25°C)	

Maximum (No Damage) Ratings	
Storage Temperature	-65°C to +125°C
Operating Temperature (Case)	-55°C to +85°C
DC Voltage @ 25°C	+18 VDC

# Multiplied Phase Locked Oscillator

256 MHz  
Model BXMF1026

## Outline Drawing



Rev 3.28.12